

Technical cross-section diagram of a roof edge detail, showing the transition from the roof slope to the vertical wall and the horizontal base. The diagram includes the following components and labels:

- Dimensions:**
 - 100 (Horizontal distance from the vertical wall to the center of the first nail)
 - 20 (Thickness of the vertical wall)
 - 100程度 (Approximate vertical distance between the first and third nails)
 - 40 (Height of the vertical wall above the base)
 - 100 (Horizontal distance from the vertical wall to the center of the second nail)
 - 100 (Vertical distance from the base to the center of the second nail)
- Labels and Components:**
 - シーリング (シーリング工事) (Sealing (Sealing work))
 - 捨てシーリング (シーリング工事) (Throwaway sealing (Sealing work))
 - 水切り：屋根同材曲げ加工 (Water cutoff: Roofing material bending work)
 - 取合い水切り：屋根同材 (Fitting water cutoff: Roofing material)
 - アポロルーフ (Apollo Roof)
 - 屋根材立ち上げ (Roofing material standing up)
 - 捨て板 (Throwaway board)
 - HEX $\phi 5$ (Hexagonal bolt $\phi 5$)
 - 野地板 (910 \times 1,820) (Subfloor (910 \times 1,820))
 - アスファルトルーフィング940 (Asphalt roofing 940)

訂正	版数	年月日		版数	年月日		設計監理	承諾印	施 工	承諾印	NSSB奥平スチール 株式会社	発行	担 当	名 称	図 面 No.
	①			①								作 成	製 図	図面名	
	②			②								壁取合 (2) 断面図 縮 尺 A1-1/ A3-1/3			
	③			③											
	④			④											
							殿		殿	AP-200-09					